

[2016-New Free Lead2pass Cisco 400-101 VCE And PDF Instant Download (1-10)]

2016 July Cisco Official New Released 400-101 Q&As in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! How to pass 400-101 exam easily? Are you struggling for the 400-101 exam? Good news, Lead2pass Cisco technical experts have collected all the questions and answers which are updated to cover the knowledge points and enhance candidates' abilities. We offer the latest 400-101 PDF and VCE dumps with new version VCE player for free download, and the new 400-101 practice test ensures your 400-101 exam 100% pass. Following questions and answers are all new published by Cisco Official Exam Center:

<http://www.lead2pass.com/400-101.html> QUESTION 1 In which order of magnitude (time) is delay/latency measured when you use wide metrics in EIGRP? A. tens of microseconds B. picoseconds C. nanoseconds D. microseconds Answer: B
QUESTION 2 Which statement about the BGP synchronization rule is true? A. A BGP router with synchronization enabled does not advertise its iBGP learned routes to its iBGP peers unless it has learned or verified this route on its routing table through an IGP. B. A BGP router with synchronization enabled does not advertise its eBGP learned routes to its iBGP peers unless it has learned or verified this route on its routing table through an IGP. C. A BGP router with synchronization enabled does not advertise its eBGP learned routes to its eBGP peers unless it has learned or verified this route on its routing table through an IGP. D. A BGP router with synchronization enabled does not advertise its iBGP learned routes to its eBGP peers unless it has learned or verified this route on its routing table through an IGP. Answer: D
QUESTION 3 Which tunnel type can be used with encryption to provide security for IPv6 over IPv4? A. 6RD B. 6to4 C. ISATAP D. IPv4-compatible E. GRE Answer: E
QUESTION 4 Which QoS mechanism is used to implement CoPP? A. RSVP B. rate limiting C. FIFO D. MQC Answer: D
QUESTION 5 Which two statements about the spanning-tree timers in a switched network are true? (Choose two) A. After receiving a BPDU from the root bridge, a non-root bridge waits for the hello interval before forwarding it out. B. The root bridge sends out a TCN every max-age interval. C. The root bridge sends out a configuration BPDU every hello interval. D. The default hello time is two seconds. Answer: CD
QUESTION 6 Which two statements about Cisco IOS XE are true? (Choose two) A. Separate images are required for platform-dependent code. B. Its functions run as multiple separate processes in the OS. C. It uses a service blade outside Cisco IOS XE to integrate and run applications. D. It is deployed in a Linux-based environment. E. The FED feature provides separation between the control plane and the data plane. Answer: BD
QUESTION 7 Which two factors can reduce NBAR2 performance? (Choose two) A. queuing B. multiple NBAR2-enabled interfaces C. slow link speeds D. stateful protocol matches E. short-duration flows Answer: DE
QUESTION 8 Which encryption algorithm is enabled by the Cisco IOS command service password-encryption? A. MD5 B. Cisco Type-5 C. Cisco AES D. Cisco Type-7 E. TKIP Answer: D
QUESTION 9 Which two options are requirements for AToM support? (Choose two) A. Cisco Express Forwarding must be disabled. B. MPLS must be configured with an LSP in the SP core. C. MPLS must be enabled between the PE and CE routers. D. The PE routers must be able to communicate with each other over IP. E. IP routing must be configured between the PE and CE routers. Answer: BD
QUESTION 10 Which two statements best describes the difference between active mode monitoring and passive mode monitoring? (Choose two.) A. Active mode monitoring is the act of Cisco PfR gathering information on user packets assembled into flows by NetFlow. B. Active mode monitoring uses IP SLA probes for obtaining performance characteristics of the current exit WAN link. C. Passive mode monitoring uses IP SLA to generate probes for the purpose of obtaining information regarding the characteristics of the WAN links. D. Passive mode monitoring uses NetFlow for obtaining performance characteristics of the exit WAN links. Answer: BD
Lead2pass Cisco 400-101 exam dumps are audited by our certified subject matter experts and published authors for development. Lead2pass Cisco 400-101 exam dumps are one of the highest quality Cisco 400-101 Q&As in the world. It covers nearly 96% real questions and answers, including the entire testing scope. Lead2pass guarantees you pass Cisco 400-101 exam at first attempt. 2016 Cisco 400-101 exam dumps (All 1119 Q&As) from Lead2pass:
<http://www.lead2pass.com/400-101.html> [100% Exam Pass Guaranteed]