

Free Download Latest 2014 Pass4sure&Lead2pass Juniper JN0-694 Dumps

Vendor: JuniperExam Code: JN0-694Exam Name: Juniper Networks Certified Support Professional (JNCSP-ENT) QUESTION 1Referring to the exhibit, why are the OSPF routes missing from the routing table for this router?user@router> show ospf databaseArea 0.0.0.1Type ID Adv Rtr Seq Age Opt Cksum LenRouter 172.24.255.1 172.24.255.1 0x800000d4 182 0x22 0x59f3 36Router 172.24.255.2 172.24.255.2 0x800000d4 177 0x22 0x57f2 36Router *172.24.255.4 172.24.255.4 0x800000dc 176 0x22 0x75fa 72Network 172.24.124.2 172.24.255.2 0x80000007 177 0x22 0x7957 36Summary 172.24.13.0 172.24.255.1 0x80000004 2370 0x22 0x3f62 28Summary 172.24.23.0 172.24.255.1 0x80000002 471 0x22 0xdeb9 28Summary 172.24.255.1 172.24.255.1 0x800000cb 2037 0x22 0x2bbb 28Summary 172.24.255.2 172.24.255.2 0x800000cc 487 0x22 0x19ca 28Summary 172.24.255.3 172.24.255.1 0x80000003 140 0x22 0xb2f9 28OSPF AS SCOPE link state databaseType ID Adv Rtr Seq Age Opt Cksum LenExtern *1.47.82.0 172.24.255.4 0x80000002 1037 0x22 0x4225 36Extern *100.0.0.0 172.24.255.4 0x80000001 2643 0x22 0xfc88 36user@router> show ospf neighborAddress Interface State ID Pri Dead172.24.124.2 ge-0/0/1.0 Full 172.24.255.2 128 36172.24.124.1 ge-0/0/1.0 Full 172.24.255.1 128 30user@router> show ospf interface ge-0/0/1.0 extensiveInterface State Area DR ID BDR ID Nbrsge-0/0/1.0 PtToPt 0.0.0.1 0.0.0.0 0.0.0.0 2Type: P2MP, Address: 172.24.124.4, Mask: 255.255.255.0, MTU: 1500, Cost: 1Adj count: 2Hello: 10, DeaD. 40, ReXmit: 5, Not StubAuth type: NoneProtection type: NoneTopology default (ID 0) -> Cost: 1 A. mismatching OSPF interface type with the neighborB. MTU mismatch with the neighborC. incorrect IP address configured on the interfaceD. no Type 4 LSAs in the OSPF database Answer: A QUESTION 2You notice that there is a problem with the OSPF adjacency between two routers, R1 and R2. The relevant system logs from R1 are shown in the exhibit.What would cause this behavior?Jun 12 02:56:06 R1 rpd[60735]: RPD_OSPF_NBRDOWN: OSPF neighbor 10.50.10.25 (realmospf-v2 fe-0/0/4.0 area 0.0.0.0) state changed from Full to Init due to 1WayRcvd (event reason:neighbor is in one-way mode)Jun 12 02:59:36 R1 rpd[60735]: RPD_OSPF_NBRUP: OSPF neighbor 10.50.10.25 (realm ospf-v2 fe-0/0/4.0 area 0.0.0.0) state changed from Init to ExStart due to 2WayRcvd (event reason:neighbor detected this router)Jun 12 02:59:36 R1 rpd[60735]: RPD_OSPF_NBRUP: OSPF neighbor 10.50.10.25 (realm ospfv2fe-0/0/4.0 area 0.0.0.0) state changed from Exchange to Full due to ExchangeDone (eventreason: DBD exchange of slave completed) A. R2 was dropping R1's OSPF hello packets.B. R1 was dropping R2's OSPF hello packets.C. R1's interface went down and came back up.D. There is an OSPF hello timer mismatch between the two routers. Answer: A QUESTION 3Referring to the exhibit, you are configuring an OSPF network. All OSPF adjacencies come up and stay stable. But neither R1 nor R2 has the prefix 200.200.200.200/32 in its routing table.What is causing this problem?

```

user@R1> show route
inet.0: 5 destinations, 5 routes (5 active, 0
holddown, 0 hidden)
+ = Active Route, - = Last Active, * = Both
1.1.1.1/32      *[Direct/0] 00:01:10
                > via lo0.0
2.2.2.2/32      *[OSPF/10] 00:00:13, metric 1
                > to 172.10.1.2 via ge-0/0/1.0
172.10.1.0/24   *[Direct/0] 00:01:10
                > via ge-0/0/1.0
172.10.1.1/32   *[Local/0] 00:01:10
                Local via ge-0/0/1.0
224.0.0.5/32    *[OSPF/10] 00:01:10, metric 1
                MultiRecv

user@R1> show ospf database
Jun 12 03:33:34
OSPF database, Area 0.0.0.0
Type ID Adv Rtr Seq Age Opt Cksum Len
Router 2.2.2.2 2.2.2.2 0x80000005 30 0x22 0xeb10 60
Router *200.200.200.200 200.200.200.200 0x80000009 7 0x22 0x1d42 48
Network *172.10.1.1 200.200.200.200 0x80000005 2 0x22 0xcc62 32
Network *172.20.1.3 200.200.200.200 0x80000004 3600 0x22 0x42e1 32

user@R1> show ospf database
Jun 12 03:33:46
OSPF database, Area 0.0.0.0
Type ID Adv Rtr Seq Age Opt Cksum Len
Router 2.2.2.2 2.2.2.2 0x80000005 42 0x22 0xeb10 60
Router *200.200.200.200 200.200.200.200 0x8000000d 3 0x22 0x1545 48
Network *172.10.1.1 200.200.200.200 0x80000006 6 0x22 0x42e1 32
Network *172.20.1.3 200.200.200.200 0x80000005 3600 0x22 0x42e1 32
    
```

A. R2 does not have the export policy for prefix 200.200.200.200/32.B. R1 does not have routes to network 172.10.1.0/24.C. R2 is BDR on both network 172.10.1.0/24 and 172.20.1.0/24.D. The router ID of R1 is the same as the router ID of R3. Answer: D QUESTION 4You are troubleshooting an OSPF adjacency problem between R1 and R2.Referring to the exhibit, what is causing this OSPF adjacency problem?



```

user@R1# show protocols ospf
area 0.0.0.0 {
  interface ge-0/0/2.0 {
    hello-interval 10;
    dead-interval 40;
  }
}
[edit]
user@R1# show interfaces ge-0/0/2
mtu 1500;
unit 0 {
  family inet {
    address 192.168.1.1/24;
  }
}
  
```

```

user@R2# show protocols ospf
area 0.0.0.0 {
  interface ge-0/0/2.0;
}
[edit]
user@R2# show interfaces ge-0/0/2
unit 0 {
  family inet {
    address 192.168.1.2/24;
  }
}
  
```

lead2pass.com

A. There is a hello interval mismatch. B. There is a dead interval mismatch. C. There is an MTU mismatch. D. There is an LSA refresh timer mismatch. Answer: C

QUESTION 5 You are trying to establish an OSPF adjacency between R1 and R2, but the adjacency does not establish. Referring to the exhibit, what is causing the adjacency to fail?

```

user@R1> show ospf neighbor
Address Interface State ID Pri Dead
10.222.0.2 ge-0/0/1.0 Init 10.222.1.2 128 32
user@R1> show ospf interface detail
Interface State Area DR ID BDR ID Nbrs
ge-0/0/1.0 DR 0.0.0.0 10.222.1.1 0.0.0.0 1
Type: LAN, Address: 10.222.0.1, Mask: 255.255.255.252, MTU: 1500, Cost: 1
DR addr: 10.222.0.1, Priority: 128
Adj count: 0
Hello: 10, DeaD. 40, ReXmit: 5, Not Stub
Auth type: MD5, Active key ID. 10, Start time: 1970 Jan 1 00:00:00 UTC
Protection type: None
Topology default (ID 0) -> Cost: 1
lo0.0 DR 0.0.0.0 10.222.1.1 0.0.0.0 0
Type: LAN, Address: 10.222.1.1, Mask: 255.255.255.255, MTU: 65535, Cost: 0
DR addr: 10.222.1.1, Priority: 128
Adj count: 0
Hello: 10, DeaD. 40, ReXmit: 5, Not Stub
Auth type: None
Protection type: None
Topology default (ID 0) -> Cost: 0
user@R2> show ospf neighbor
user@R2> show ospf interface detail
Interface State Area DR ID BDR ID Nbrs
ge-0/0/1.0 PtToPt 0.0.0.0 0.0.0.0 0.0.0.0 0
Type: P2P, Address: 10.222.0.2, Mask: 255.255.255.252, MTU: 1500, Cost: 1
Adj count: 0
Hello: 10, DeaD. 40, ReXmit: 5, Not Stub
Auth type: MD5, Active key ID. 10, Start time: 1970 Jan 1 00:00:00 UTC
Protection type: None
Topology default (ID 0) -> Cost: 1
lo0.0 DR 0.0.0.0 10.222.1.2 0.0.0.0 0
Type: LAN, Address: 10.222.1.2, Mask: 255.255.255.255, MTU: 65535, Cost: 0
DR addr: 10.222.1.2, Priority: 128
Adj count: 0
Hello: 10, DeaD. 40, ReXmit: 5, Not Stub
Auth type: None
Protection A. The MD5 key ID values are mismatched between R1 and R2.
B. R1 has both family inet and family iso configured on the link toward R2.
C. The IP subnet mask is mismatched between R1 and R2.
D. The interface type is mismatched between R1 and R2. Answer: D
  
```

If you want to pass Juniper JN0-694 successfully, don't miss to read latest lead2pass Juniper JN0-694 dumps. If you can master all lead2pass questions you will be able to pass 100% guaranteed. <http://www.lead2pass.com/JN0-694.html>