

[Lead2pass New Free Lead2pass Cisco 400-051 PDF Dumps With The Latest Update Exam Questions (421-440)]

2017 November Cisco Official New Released 400-051 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed!

Lead2pass 400-051 braindumps including the exam questions and the answer, completed by our senior IT lecturers and the Cisco product experts, include the current newest 400-051 exam questions. Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/400-051.html>

QUESTION 421 A Call is made between two desk phones enabled with single number reach that are registered to a cisco unified CM cluster. The device pool for each device has a local route group defined. When the call is placed to exit the system, which device pool control the destination gateway? A. Destination RDPB. Source PhoneC. Source RDPD. Destination phoneAnswer: B

QUESTION 422 Refer to the exhibit. Which three facts can be determined about the audio parameters of this call from this session description protocol? (Choose Three) A. The DTMF relay will be RFC2833B. The codec will be G711C. The codec will be G729D. VAD will be disabled for this callE. VAD will be enabled for this callF. The call will be a T38 fax call Answer: ACD

QUESTION 423 Which two SCCP call states support the Meet Me soft key? (Choose two.) A. On HookB. ConnectedC. On HoldD. Off HookE. Ring OutF. Connected Conference Answer: AD

QUESTION 424 A Jabber for window user is on a call with cisco telepresence EX90 endpoint at the same location. During the call, the video on the jabber for Windows application was high quality but the video on the EX90 was choppy and slow. When the administrator checked the service rate on the EX90 it showed 2048 Kbps. Which two configuration changes can fix this problem? A. Lower the bit rate in the region configuration in communication manager between the endpoints.B. Increase the location bandwidth for immersive video between the endpointsC. Enable BFCP in the SIP profile for the jabber clientD. Enable H.263 on the EX90E. Replace the camera for the jabber user with the precision HD USB cameraF. Increase the bandwidth between the jabber video client and the EX90 Answer: EF

QUESTION 425 Refer to the exhibit. An engineer mapped the enhanced location call admission control configuration to match the physical links bandwidth allowances. Assuming no other calls are consuming any bandwidth, how many G722 calls are allowed between site A and site G? A. 5B. 7C. 12D. 25E. 37 Answer: B

QUESTION 426 Refer to the exhibit. Which SIP message will trigger the calling device to open channels for early media reception? A. 180 RingingB. ACKC. INVITED. 183 session-progressE. 200 OK Answer: D

QUESTION 427 Refer to the exhibit. A network engineer is troubleshooting a NTP synchronized issue in CUCM. Why is NTP Unsynchronized? A. The NTP server used is a Windows based NTP serverB. The IOS Command NTP server 172.25.140.151 version 3 is advertising NTPv3C. The NTP server stratum is higher than fourD. A firewall is blocking NTP port 123 Answer: A

QUESTION 428 Refer to the exhibit. A Cisco collaboration engineer is writing a report to summarize the call distribution characteristics in a Cisco Unified Contact Centre Express queue. Which three characteristics can be reported about the call distribution? (Choose three.) A. This queue will not work because no prompt has been selected.B. Calls to this queue can be distributed in a round-robin manner between agents.C. Agents that are answering calls for this queue can answer calls to other queues if available.D. Agents in this queue are expected to finish (wrap-up) a call within 60 seconds.E. Calls to this queue are handled in the order they were received unless prioritized by the script.F. Changing the queue name from SupportQueue to Support01 requires updates to the script.G. Agents logged in to this queue automatically receive calls without the need to do anything else (Automatic work). Answer: CEF

QUESTION 429 A cisco Unified CM engineer configured a phone VPN for remote users but the users cannot register the phones to the VPN. Which configuration change fixes this problem? A. Configure enable outside in the webVPN configuration on the Cisco ASAB. Configure the split-tunnel-policy tunnel all attribute on the Cisco ASAC. Configure the ssl trust-point SSL outside on the Cisco ASAD. Remove the Cisco ASA IP address from the VPN load-balancing configuration Answer: D

QUESTION 430 Refer to the Exhibit. An Engineer is troubleshooting transcoding issue in a remote branch office after a WAN outage. All IP phones can register to a CME in SRST 2900 ISR Router however, the users reported that calls disconnect after pressing the answer soft key. Which three configuration are necessary for successful media resource failover? (Choose three) A. SCCP ccm group 1Associate ccm 3 priority 1B. SCCP ccm 10.1.1.2identifier 3 version 7.0C. Telephony-serviceSdspfarm units 1Sdspfarm tag 1XD-REMOTED. Sccp ccm 10.1.1.2identifier 1 version 7.0E. Associate profile 3register XD-REMOTE2F. Sccp ccm group 1Associate ccm 3 priority 3 Answer: BCF

QUESTION 431 Refer to the exhibit. A collaboration engineer is configuring device mobility. Which three events occur to phone A1 When it moves to physical location B? (Choose three) A. Phone A PSTN calls preserve home location dialling behaviourB. Phone A inherits CSS from roaming device pool DP_B2C. Phone A PSTN calls Adopts roaming location dialling behaviourD. Phone A retains CSS from Home device pool DP_A1E. Phone A retains media Resource group list from home device pool DP_A1F. Phone A inherits media resource group list from roaming device pool DP_B2 Answer: ADE

QUESTION 432 Refer to the exhibit. A network engineer is troubleshooting a call routing issue where failed

calls on the primary path (SiteA-RTR) was not sent to the secondary path (SiteC-RTR). Why is CUCM unable to extend the call setup through SiteC-RTR? A. Stop routing on Q.931 Disconnect cause code is set to 27B. Stop routing on Unallocated Number Flag is set to trueC. Stop Routing on User Busy Flag is set to trueD. Retry count for SIP Invite is set to 1E. Retry count for SIP response is set to 1 Answer: B QUESTION 433Which definition is included in a Cisco UC on UCS TRC? A. Required RAID configuration When TRC uses direct attached storageB. Configuration of virtual-to-physical network interface mappingC. Step-by-step procedures for hardware BIOS, firmware, drivers, and RAID setupD. Server model and local components (CPU, RAM, adapters, local storage) by name only. Part numbers are not included because they change over timeE. Configuration settings and patch recommendations for VMware software Answer: A QUESTION 434Refer to the exhibit. A phone VPN failed to establish a VPN with the Cisco ASA. The support engineer downloaded the console logs and analysed them. When two steps resolve this issue? (Choose two) A. Configure user and password authentication instead of certificate onlyB. Uncheck the enable Host ID check checkbox under the VPN profile in Cisco Unified CMC. Reset the Cisco Unified CM TFTP service to allow caching of the new certificateD. Delete the current certificate so the phone can download a new oneE. Register the phone internally to download the new configuration Answer: BE QUESTION 435Refer to the exhibit. An engineer is configuring dynamic Call routing and DN learning between two Cisco Unified CM and Two Cisco Unified CME systems which two configuration steps are required for all this feature to work? (Choose two) A. Configure routers A and B to use a different autonomous system number for DN routingB. Configure routers A and B to use EIGRP for IP RoutingC. Configure Cisco Unified CM A+B as service advertisement framework clientsD. Configure router A and B to use OSPF for IP RoutingE. Configure Cisco Unified CME A+B as service advertisements forwardersF. Configure routers A and B to use the same autonomous system number for DN Routing Answer: CF QUESTION 436Refer to the exhibit. A carrier delivers a SIP call to cisco Unified CM through a Cisco Unified border Elements with The Invite destination different than "To" field. The Unified CM Administration engineer sees that the calls go to the invite destination instead of the "To" field Unified CM. Which option shows how the engineer correct that problem in the Cisco Unified border Elements router? A. B. C. D. Answer: A QUESTION 437A Cisco collaboration architect is evaluating a list of codecs to use in a voice infrastructure. Which three facts are associated with iSAC and should be considered in the decision? (Choose three) A. The codec has better quality with less bandwidth for sideband applicationsB. The codec will not be supported in TDM voice gatewaysC. The codec will adjust its bandwidth consumption to the network conditionsD. The codec will not be available for H.323 and MGCP devicesE. The codec will not support low complexityF. The codec will not be supported by SCCP configured on DSPFARMS Answer: ACE QUESTION 438Refer to the Exhibit. An agent initiated a video call but was establish as audio only. The support engineer collected and analysed the Cisco Unified CM traces.Which two options caused this problem? (Choose two) A. A hardware MTP was assigned to the callB. SIP Notify DTMF was requested and negotiatedC. MTP required was checked on the SIP TrunksD. Use Trusted Relay Point is set on one of the phoneE. MRGL assigned to phones with Trusted Relay Point Answer: DE QUESTION 439Refer to the exhibit. A collaboration engineer is troubleshooting a cluster that has been configured to use RSVP. The calls are being rejected and the caller receives a busy tone. What is the root cause of this problem? A. The RSVP Agents are only using an Ipv6 address.B. The IP Addressing mode preference for signalling is set to use System Default.C. The RSVP relationship between Main and Remote is set to MandatoryD. The IP Addressing Mode is set to use Ipv4 and Ipv6 Answer: A QUESTION 440Refer to the exhibit. Which three pieces of information can be derived from this sip message? (Choose Three) A. The call will have no audioB. Only OOB DTMF will be supportedC. G722 codec will be chosenD. The B2BUA uses IP 172.16.100.50E. This is a flow-around configurationF. The call will last only 30 minutes Answer: BDF If you use Lead2pass braindump as your 400-051 exam prepare material, we guarantee your success in the first attempt. Lead2pass 400-051 dump provides you everything you will need to take your 400-051 Exam. 400-051 new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDcVpjV1ZNcjVzaW8> 2017 Cisco 400-051 exam dumps (All 542 Q&As) from Lead2pass: <http://www.lead2pass.com/400-051.html> [100% Exam Pass Guaranteed]