

[Q21-Q30 Lead2pass 2017 100% Real 300-180 Exam Questions

Lead2pass 2017 New Cisco 300-180 Braindump Free Download: <https://www.lead2pass.com/300-180.html> QUESTION 21 What is the recommended procedure to update Cisco UCS C-Series rack-mount server firmware? A. Launch the Cisco UCS Firmware Update Utility from virtual media. B. Launch the Cisco UCS Host Update Utility from virtual media. C. Launch the Cisco UCS Server Update Utility from virtual media. D. Launch the Cisco UCS CIMC Update Utility from virtual media. Answer: B QUESTION 22 300-180 Dumps, 300-180 Exam Questions, 300-180 New Questions, 300-180 VCE, 300-180 PDF You are installing Microsoft Windows Server 2008 R2 on a Cisco UCS C210 M2 server, and the installer does not see local storage on the LSI MegaRAID SAS 9260-4i controller that is installed. Which statement explains the issue? A. The driver is not included in the installer DVD. Press F6 to load the LSI RAID driver from CD or virtual media. B. The virtual disk is not created and online. C. The LSI 9260-4i is only supported by Red Hat Enterprise Linux and VMware vSphere 4.0 and later. D. The installer DVD for Microsoft Windows Server 2008 R2 did not include the LSI driver until SP2. Answer: B QUESTION 23 300-180 Dumps, 300-180 Exam Questions, 300-180 New Questions, 300-180 VCE, 300-180 PDF Which CLI command will indicate whether a Cisco UCS C-Series rack-mount server has any failed DIMMs? A. `ucs-c250 / # scope chassis ucs-c250 / chassis # show dimm-summary` B. `ucs-c250 / # scope chassis ucs-c250 / chassis # show dimm-fault` C. `ucs-c250 / # scope chassis ucs-c250 / chassis # show dimm-ecc` D. `ucs-c250 / # scope chassis ucs-c250 / chassis # show dimm-recovery` Answer: A QUESTION 24 300-180 Dumps, 300-180 Exam Questions, 300-180 New Questions, 300-180 VCE, 300-180 PDF You successfully install VMware ESXi 5.0 U1 on a Cisco UCS B200 M3 server to a Fibre Channel LUN. When you reboot the server, you see the message "Reboot and Select Proper Boot device or insert Boot Media in selected Boot device and press a key." What are the first two pieces of information you should gather to troubleshoot the boot failure? (Choose two.) A. Connect to the NX-OS shell via the CLI and run the `show npv flogi-table` command. B. SSH to the MDS 9124 and run the `show flogi database` command. C. Validate the boot target WWPN and LUN ID in the service profile. D. Validate the correct source WWPN in the service profile vHBA definition. E. Validate zoning for your WWPN on the Cisco MDS 9124. F. Validate that the boot order indicates the vHBA as the first device. G. Ensure LUN masking is correctly configured on the storage controller. Answer: CF QUESTION 25 300-180 Dumps, 300-180 Exam Questions, 300-180 New Questions, 300-180 VCE, 300-180 PDF A customer calls in a trouble ticket complaining of unacceptable read I/O latency on a Cisco UCS C210 M2 server with an LSI MegaRAID 9260-8i with an 8-disk RAID-10 virtual disk. As you validate the RAID controller configuration, which of these configured items impacts read performance at the controller level? A. all disks are 146GB 6 Gb SAS 15K RPM SFFB. B. read ahead cache is enabled. C. BGI rate = 0D. D. strip size = 256kE. E. no hot spare Answer: D QUESTION 26 300-180 Dumps, 300-180 Exam Questions, 300-180 New Questions, 300-180 VCE, 300-180 PDF You are troubleshooting an FCoE SAN boot issue on a Cisco UCS C240 M3 server with a VIC 1225. Which two of these represent the correct way to bind VSAN 11 to interface vfc5 attached to interface Ethernet 1/5? (Choose two.) A. `5548UP(config)# int vfc 5548UP(config-if)# bind interface Ethernet1/5 vsan 11` B. `5548UP(config)# vsan database 5548UP(config-vsan-db)# vsan 11 interface vfc5` C. `5548UP(config)# interface Ethernet1/5 5548UP(config-if)# bind vsan 11` D. `5548UP(config)# vsan database 5548UP(config-vsan-db)# bind interface vfc5 vsan 11` E. `5548UP(config)# vsan database 5548UP(config-vsan-db)# interface vfc5 vsan 11` F. `5548UP(config)# vsan database 5548UP(config-vsan-db)# interface Ethernet1/5 vsan 11` Answer: AB QUESTION 27 300-180 Dumps, 300-180 Exam Questions, 300-180 New Questions, 300-180 VCE, 300-180 PDF You are troubleshooting an FCoE boot issue on a Cisco UCS C220 M3 server with a VIC 1225CNA. Which two pieces of information can you directly infer from the output of the `show zoneactive` command below? (Choose two.) `zone name Server_1-to-Storage vsan 11 pwwn 50:06:01:60:3b:a0:08:9f [Storage]* fcid 0x3b000b [pwwn 20:00:00:25:b5:04:0a:02] [C22_Server]` A. The storage controller is not logged into the fabric. B. The server is not logged into the fabric. C. Only the storage controller is logged into the fabric. D. Only the server is logged into the fabric. E. The initiator and target cannot communicate because they are on the wrong VSAN. F. The WWPN of the storage controller is mistyped. G. The initiator and target cannot communicate because the zone name does not match the server name (C22_Server). Answer: AD QUESTION 28 300-180 Dumps, 300-180 Exam Questions, 300-180 New Questions, 300-180 VCE, 300-180 PDF Which statement is true with respect to resetting a forgotten Cisco IMC admin password on a Cisco UCS C-Series rack-mount server? A. Download the Cisco IMC password reset utility ISO file from Cisco.com and boot from virtual media. The server will boot the Linux Live CD and reset the password to 'password'. B. Download the Cisco IMC password reset EFI plugin file from Cisco.com to a USB flash drive and boot to the EFI shell. The startup.nsh file will auto-load and reset the password to 'password'. C. Shut down the server and remove all power supplies for 3 minutes to allow the password capacitor to discharge. Use the default password 'password' to log back in. D. Shut down the server and remove all power cords. Open the case and short the jumper specified in the model-specific Cisco UCS C-Series Server

Installation and Service Guide. Answer: D QUESTION 29 300-180 Dumps,300-180 Exam Questions,300-180 New Questions,300-180 VCE,300-180 PDFWhich four tasks can be performed via Cisco IMC remote access to a Cisco UCS system? (Choose four.) A. power cycle the serverB. deploy an operating systemC. toggle the locator LEDD. configure the boot orderE. view properties and sensorsF. configure the hypervisorG. enable Cisco UCS Manager Answer: ACDE QUESTION 30 300-180 Dumps,300-180 Exam Questions,300-180 New Questions,300-180 VCE,300-180 PDFWhich remote access protocol is used by default to obtain CLI access to a Cisco UCS C-Series standalone server? A. TelnetB. SSHC. HTTPD. SSLE. SOCKS Answer: B **300-180 dumps full version (PDF&VCE): <https://www.lead2pass.com/300-180.html> Large amount of free 300-180 exam questions on Google Drive: <https://drive.google.com/open?id=108Bd0NBc2wWwiFC-bUg8eLE5zS0n9gVN> You may also need: 300-165 exam dumps: <https://drive.google.com/open?id=0B3Syig5i8gpDSkhBVngxX0Z3Y0k> 300-170 exam dumps: <https://drive.google.com/open?id=0B3Syig5i8gpDdHhmcTB1bGM4bmc> 300-175 exam dumps: <https://drive.google.com/open?id=0B3Syig5i8gpDVDYyRldqb1AzenM>**